


City of Brentwood Standard Plans and Specifications

TABLE OF CONTENTS


STANDARD DETAILS

CATHODIC PROTECTION (CP)

CORROSION TEST STATION (CTS)	CP-1
ANODE TEST STATION (ATS)	CP-2
CASING TEST STATION (CTS)	CP-3
FOREIGN PIPELINE TEST STATION (FPTS)	CP-4
INSULATING JOINT TEST STATION (IJTS)	CP-5
ANODE TEST STATION – CROSS	CP-6
ANODE TEST STATION – ELBOW	CP-7
ANODE TEST STATION – FIRE HYDRANT	CP-8
ANODE TEST STATION – RISER	CP-9
ANODE TEST STATION – VALVE	CP-10
ANODE TEST STATION – VALVE & TEE	CP-11
ANODE TEST STATION – LATERAL	CP-12
TEST STATION	CP-13
DIELECTRIC INSULATING JOINT	CP-14
CABLE IDENTIFICATION	CP-15
EXOTHERMIC WELD PROCESS	CP-16
WENNER FOUR PIN RESISTIVITY TEST	CP-17



CTS TERMINAL BOX



NOTES:

- 1. IDENTIFY CABLES PER STANDARD PLAN CP-15.
- 2. LOCATION TO BE SHOWN ON THE PLANS OR AS DIRECTED BY THE CITY ENGINEER.

(Not To Scale)





ENGINEERING DEPARTMENT



CORROSION TEST STATION (CTS)

BALWINDER S. GREWAL CITY ENGINEER REVISED: DEC. 31, 2013





IDENTIFY CABLES PER STANDARD PLAN CP-15.

(Not To Scale)



ENGINEERING DEPARTMENT




ANODE TEST STATION (ATS)


BALWINGER S. GREWAL CITY ENGINEER

DATE: JUNE 15, 2003

REVISED: DEC. 31, 2013



CATS TERMINAL BOX



NOTES:

- CARRIER PIPE & CASING SHALL BE ELECTRICALLY ISOLATED VIA CASING INSULATORS.
- 2. ON A NON-METALLIC CARRIER PIPE, DELETE WHITE CABLES AND EXOTHERMIC WELDS.
- 3. IDENTIFY CABLES PER STANDARD PLAN CP-15.

(Not To Scale)



ENGINEERING DEPARTMENT





CASING TEST STATION - CATS

BALWINGER S. GREWAL CITY ENGINEER

DATE: JUNE 20, 2003

REVISED: DEC. 31, 2013





- 1. IDENTIFY CABLES PER STANDARD PLAN CP-15.
- 2. THE REFERENCE CELL SHALL BE INSTALLED BETWEEN THE TWO PIPES.

(Not To Scale)




ENGINEERING DEPARTMENT




FOREIGN PIPELINE TEST STATION (FPTS)

(28)	_	DATE:	JUNE 20, 2003	SHEET No.
Do ver		DATE.	JOINE 20, 2003	CP_{-4}
BALWINDER S. GREWAL	CITY ENGINEER	REVISED:	DEC. 31, 2013	



IJTS TERMINAL BOX



(Not To Scale)




ENGINEERING DEPARTMENT




INSULATING JOINT TEST STATION (IJTS)

Byren	
BALWINDER S. GREWAL	CITY ENGINEER

DATE:	JUNE 20, 2003
REVISED:	DEC. 31, 2013



- 1. IDENTIFY CABLES PER CP-15.
- 2. TEST STATIONS MAY BE DELETED AT THE DISCRETION OF THE CITY ENGINEER. IF THE TEST STATION IS DELETED, CONNECT ANODE DIRECTLY TO THE FITTING PER CP-16.
- 3. TEST STATIONS SHALL BE SET BEHIND CURB OR SIDEWALK.



TERMINAL BOX (COVER NOT SHOWN FOR CLARITY)

0.01 OHM/6 AMP SHUNT

- (1) #10 AWG/THHN ANODE CABLE (BLACK)
- (1) #10 AWG/THHN DRAIN CABLE (WHITE)
- (1) #10 AWG/THHN TEST CABLE (WHITE)

ATS TERMINAL BOX

(Not To Scale)



ENGINEERING DEPARTMENT




ANODE TEST STATION - CROSS

BALWINDER S. GREWAL CITY ENGINEER

DATE: JUNE 20, 2003

REVISED: DEC. 31, 2013



- 1. FOR TERMINAL BOX WIRING SEE STANDARD PLAN CP-6.
- 2. TEST STATION MAY BE DELETED AT THE DISCRETION OF THE CITY ENGINEER. IF THE TEST STATION IS DELETED, CONNECT THE ANODE LEAD DIRECTLY TO THE FITTING PER STANDARD PLAN CP-16.
- 3. ALL TEST STATIONS SHALL BE SET BEHIND CURB OR SIDEWALK.

(Not To Scale)




ENGINEERING DEPARTMENT



ANODE TEST STATION - ELBOW

Byen	
BALWINDER S. GREWAL	CITY ENGINEER

DATE:	JUNE 20, 2003
REVISED:	DEC. 31, 2013



- 1. FOR TERMINAL BOX WIRING SEE STANDARDARD PLAN CP-6.
- 2. TEST STATION MAY BE DELETED AT THE DISCRETION OF THE CITY ENGINEER. IF THE TEST STATION IS DELETED, CONNECT THE ANODE LEAD DIRECTLY TO THE FITTING PER STANDARD PLAN CP-16.
- 3. ALL TEST STATIONS SHALL BE SET BEHIND CURB OR SIDEWALK.

(Not To Scale)



ENGINEERING DEPARTMENT




ANODE TEST STATION - FIRE HYDRANT

BALWINDER S. GREWAL CITY ENGINEER

DATE: JUNE 20, 2003

REVISED: DEC. 31, 2013



- 1. FOR TERMINAL BOX WIRING SEE STANDARD PLAN CP-6.
- TEST STATION MAY BE DELETED AT THE DISCRETION OF THE CITY ENGINEER. IF THE TEST STATION IS DELETED, CONNECT THE ANODE LEAD DIRECTLY TO THE FITTING PER STANDARD PLAN CP-16.
- 3. TEST STATIONS SHALL BE SET BEHIND CURB OR SIDEWALK.

(Not To Scale)



ENGINEERING DEPARTMENT




ANODE TEST STATION - RISER

BALWINDER S. GREWAL CITY ENGINEER REVISED

DATE: JUNE 20, 2003

REVISED: DEC. 31, 2013



- 1. INSTALL ANODE A MINIMUM 2 FEET FROM VALVE.
- 2. FOR TERMINAL BOX WIRING SEE STANDARD PLAN CP-6.
- 3. TEST STATION SHALL BE SET BEHIND CURB OR SIDEWALK.

(Not To Scale)



ENGINEERING DEPARTMENT




ANODE TEST STATION - VALVE

BALWINDER S. GREWAL CITY ENGINEER

DATE: OCT. 31, 2000

REVISED: DEC. 31, 2013







ENGINEERING DEPARTMENT




ANODE TEST STATION - VALVE AND TEE

BALWINDER S. GREWAL CITY ENGINEER

DATE: JUNE 20, 2003

REVISED: DEC. 31, 2013



- 1. IF WATERMAIN IS METALLIC, PLACE INSULATING COUPLING BETWEEN COPPER WATER LATERAL AND WATERMAIN.
- 2. A MINIMUM CLEARANCE OF 2' SHALL BE MAINTAINED BETWEEN THE ANODE AND THE LATERAL.
- 3. TOP OF ANODE SHALL BE 5' MIN. FROM THE GROUND SURFACE.
- 4. TEST STATION SHALL BE SET BEHIND CURB OR SIDEWALK.

(Not To Scale)



ENGINEERING DEPARTMENT




ANODE TEST STATION - LATERAL

BALWINDER S. GREWAL CITY ENGINEER

DATE: JUNE 20, 2003

REVISED: DEC. 31, 2013



- 1. CONCRETE COLLAR IS REQUIRED FOR TEST STATIONS PLACED IN ROADWAYS AND UNPAVED AREAS.
- 2. TEST STATION SHALL BE SET BEHIND CURB OR SIDEWALK.
- 3. INSTALL 2" DIA. PVC PIPE IN CLEAN NATIVE SOIL. FILL PIPE WITH CLEAR SOIL, FREE FROM ROCKS AND DEBRIS.
- 4. INSTALL 18" LENGTH OF 3/4" DIA. PVC PIPE TO ENSURE THAT THE TERMINAL BOX WILL REMAIN IN THE UPRIGHT POSITION. POSITION THE PIPE SO THAT THE TERMINAL BOX WILL BE AS HIGH AS POSSIBLE WITH THE CAST IRON LID STILL CLOSING PROPERLY. (Not To Scale)



ENGINEERING DEPARTMENT




TEST STATION

BALWINDER S. GREWAL CITY ENGINEER


DATE: JUL. 26, 2002 REVISED: DEC. 31, 2013

BELOW GRADE INSULATING JOINT COATING



- 1. GASKET SHALL BE FOR WATER SERVICE AND BE OF SAME PRESSURE RATING AS THE FLANGE.
- 2. DELETE COATING IF FLANGE IS ABOVE GRADE OR INSTALLED IN A VAULT.
- 3. ALL BOLTS, NUTS AND WASHERS SHALL BE 304 OR 316 STAINLESS STEEL.

EXPOSED INSULATING JOINT



NOTE: FOR BURIED INSULATING JOINTS APPLY COATING AS SHOWN ABOVE.

(Not To Scale)



ENGINEERING DEPARTMENT




DIELECTRIC INSULATING JOINT

BALWINDER S. GREWAL CITY ENGINEER

DATE: JAN. 31, 1999

REVISED: DEC. 31, 2013



RW — RAW WATER

OF — OVERFLOW DR — DRAIN

DR — DRAIN AN — ANODE

RE — REFERENCE ELECTRODE

FP — FOREIGN PIPELINE

CA - CASING

DW — DOMESTIC WATER
NPW — NON-POTABLE WATER

PIPE DIAMETER (INCHES)

(Not To Scale)



ENGINEERING DEPARTMENT





CABLE IDENTIFICATION

BALWINDER S. GREWAL CITY ENGINEER

DATE: JUNE 20, 2003

REVISED: DEC. 31, 2013





NOTE: PROCEDURE SHOWN ABOVE IS TO BE USED AS A GENERAL GUIDE ONLY. CONSULT MANUFACTURER'S LITERATURE FOR SPECIFIC INSTALLATION INSTRUCTIONS.

(Not To Scale)



ENGINEERING DEPARTMENT




EXOTHERMIC WELD PROCESS

BALWINDER S. GREWAL CITY ENGINEER

DATE: JAN.31, 1999

REVISED: DEC. 31, 2013



WHERE D = DEPTH TO BOTTOM OF PIPE

(Not To Scale)



ENGINEERING DEPARTMENT



WENNER FOUR PIN RESISTIVITY TEST

BALWINDER S. GREWAL CITY ENGINEER

DATE: JAN. 31, 1999

REVISED: DEC. 31, 2013